

ERESCO 32 MF4-C

Portable X-ray Unit 200 kV Panoramic Tube Head, air cooled

The ERESKO 32 MF4-C is a 200 kV constant potential portable X-ray tube head using state of the art switching technology with high radiation output allowing shortest exposure times thereby increasing productivity.

GE Sensing & Inspection Technologies uses the number 32 to identify the superior penetration performance of its portable X-ray unit line. This means the ERESKO

32 MF4-C is capable of penetrating 32 mm (1.26") Fe with a 2.0 density after a ten-minute exposure using AGFA STRUC-TURIX D7 film @ 700 mm (27.5") FFD.

The X-ray tube head consists of a sturdy metal-ceramic X-ray tube and high voltage generator integrated into a rugged compact housing. The air-cooled 200 kV/600 W end-grounded X-ray tube is thermally protected for extended life.

The high voltage generator generates high-stability constant potential voltage at higher efficiency than conventional line frequency equipment.

The performance of the X-ray tube and the high voltage generator is continuously monitored for protection and operational safety. An on-board real time clock facilitates fully automatic warm-up routines for optimized and time-saving tube conditioning. The flexible connecting cable is heavy-duty and light weight.

Additional Features

- Rugged construction with proven reliability
- Gas insulated high voltage section reduces size & weight
- End-grounded, metal-ceramic X-ray tube
- DC voltage operation
- Modern power electronics provides high stability
- On-board real time clock supports fully automatic warm-up
- Extended operating range from 5 kV to 200 kV enables flexible use
- Large 40° x 360° emergent beam
- Optimized air-flow cooling for efficient heat dissipation
- 100% duty cycle at 30° Celsius (86° F)
- Built-in fail-safe warning lamp
- CE certification according to EMC and Low Voltage Directives
- French Standard NFC 74 100 compliant
- Water / dust resistant in accordance with protection class IP65
- Produced under ISO 9001 certified quality management system

Standard Delivery Scope

See product info "ERESCO MF4 Control"







GE imagination at work

Technical Data

X-ray tube type	200 kV metal-ceramic with Tungsten (W) cone anode
kV range	5 - 200 kV (acc. to rating chart)
Target angle	22°
Inherent filtration	0.4 mm Fe/Ni/Co + 2 mm Al
Emergent beam	40° x 360°
Focal spot size (EN 12 543)	0.4 x 4.0 mm
Tube current	0.5 - 10 mA (3.0 mA / 200 kV)
Anode temperature, max.	100°C
Current and voltage stability	± 1%
Continuous rating	600 W
Duty cycle ($\delta_{amb} = 30^\circ \text{C}$)	100 %
Power input, max.	1.0 kVA
Weight	31 kg (68.3 lbs)
Tube head diameter	160 mm (6.3") (without rings)
Protection class	IP65
Operating Temperature	-20°C to +50°C
Storage Temperature	-30°C to +80°C

Options

- Carrying cradle
- Diaphragm / collimator attachments
- Laser centering device
- Telescope centering device
- Transport and positioning cart
- Fail-safe flashing warning lamp
- Stands and mounting kits
- Aluminium transport box
- Crawler Integration Kit



drawings not true to scale



www.gesensinginspection.com

GEIT 30175EN (11/08)

© 2008 General Electric Company. All Rights Reserved. Specifications are subject to change without notice. GE is a registered trademark of General Electric Company. Other company or product names mentioned in this document may be trademarks or registered trademarks of their respective companies, which are not affiliated with GE.

Contact: GE Sensing & Inspection Technologies GmbH, Bogenstrasse 41, 22926 Ahrensburg, Germany, T +49 (0)4102 807 0